

# MTP4 / MTP4R Mobile Printers



MTP4

## Key Features

- ✓ Rugged design
- ✓ Angled LCD display
- ✓ Fast 3" per second printing
- ✓ 6-foot drop specification
- ✓ RS-232 and USB connectivity.  
Bluetooth, or 802.11b also available.

## Rough and Rugged Mobile Printing

Designed for extreme outdoor environments

### Reliable Printing

Built to survive the real world: drop it on a concrete warehouse floor, shake it as your truck hits pothole after pothole, carry it from the truck in a rainstorm, and watch as the MTP4 just keeps on printing.

### Modular Design

Made to be customized for your specific needs: add a mag card reader, or a vehicle mount, or a variety of battery charging options, or wireless communication, all in modules that mean you don't replace the printer itself when your needs change.

### Ease of Use

The angled LCD provides human readable messages rather than blinking lights to interpret, the clamshell design with automatic media centering allows simple and easy drop-in paper loading, and intelligent Lithium Ion battery technology provides long battery life with many different charging options.

### Optional Accessories

Options include Magnetic stripe reader, vehicle cradle for docking and charging, shoulder/hand straps, fast AC charger and environmental Soft Case.

Consumables

**Mobile Printers**

Laser Printers

Line Matrix Printers

Serial Matrix Printers

## Features & Specifications

<b>Printing Technology</b>	Direct Thermal
<b>Resolution</b>	203 dots per inch
<b>Print Speed</b>	3" per second
<b>Fonts</b>	25 bitmapped, 1 scalable. Optional downloadable bitmapped and scalable fonts
<b>Print Area</b>	Maximum Width: 4.09 inches Maximum Length: Continuous
<b>Paper Specifications</b>	Paper Width: 2 inch to 4.12 inch. Roll Size: 2.25 inch O.D. Core: .75 or 1.38 inches I.D. Thickness: .002 to .0063 inches. Types: receipt paper, synthetic media, UV coated media
<b>Connectivity</b>	USB 2.0 and RS-232, Bluetooth v. 1.2 or 802.11b
<b>Physical Specifications</b>	Size: (HxWxD) 6.9"x6.3"x3.1" Weight: 2.0 lbs
<b>Operating Environment</b>	Voltage: 4.0 Ah, 7.4V battery External charging options (vehicle and AC) Meets IP54 rating Temperature: Operating: -4 to 131 F (-20 to 55 C) Storage: -22 to 149 F (-30 to 65 C)
<b>Regulatory Compliance</b>	FCC Part 15 Class B, VCCI Class B, NOM/NYCE CE compliance (Class B), C-Tick



Tally, GENICOM and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.