

7265



High speed and rugged design for easy use and heavy-duty operation

At a top speed of 900 characters per second, the 7265 keeps pace with the hectic business world where printing is time sensitive and critical. The 7265 produces multi-part invoices, shipping documents or bar code labels at a rate of 40,000 pages per month.

The 7265 is expandable to two front input tractors and can handle up to 6-part forms with a straight paper path resulting in jam-free operation.

High Throughput

- 900 characters per second/540 pages per hour in draft mode; near letter quality printing at 300 characters per second

Superior Forms Handling

- Straight paper path for reliable forms handling
- Up to 6-part forms with no skewing or jamming
- Automatically adjusts for different forms thickness
- Automatic quick-tear

Ease of Use

- Long life, 20 million character ribbon for less operator interventions

Excellent Connectivity

- Serial and parallel standard
- 10/100 Ethernet and Twinax/Coax optional

Consumables

Ink Jet Printers

Laser Printers

Line Matrix Printers

Serial Matrix Printers

Features & Specifications

Printing Technology	24-wire serial impact dot matrix (136-Column)																											
Print Speed	<table border="0"> <tr> <td>15 cpi:</td> <td>Draft</td> <td>900 cps</td> </tr> <tr> <td></td> <td>NLQ</td> <td>300 cps</td> </tr> <tr> <td></td> <td>LQ</td> <td>150 cps</td> </tr> <tr> <td>12 cpi:</td> <td>Draft</td> <td>720 cps</td> </tr> <tr> <td></td> <td>NLQ</td> <td>240 cps</td> </tr> <tr> <td></td> <td>LQ</td> <td>120 cps</td> </tr> <tr> <td>10 cpi:</td> <td>Draft</td> <td>650 cps</td> </tr> <tr> <td></td> <td>NLQ</td> <td>200 cps</td> </tr> <tr> <td></td> <td>LQ</td> <td>100 cps</td> </tr> </table>	15 cpi:	Draft	900 cps		NLQ	300 cps		LQ	150 cps	12 cpi:	Draft	720 cps		NLQ	240 cps		LQ	120 cps	10 cpi:	Draft	650 cps		NLQ	200 cps		LQ	100 cps
15 cpi:	Draft	900 cps																										
	NLQ	300 cps																										
	LQ	150 cps																										
12 cpi:	Draft	720 cps																										
	NLQ	240 cps																										
	LQ	120 cps																										
10 cpi:	Draft	650 cps																										
	NLQ	200 cps																										
	LQ	100 cps																										
Workload	40,000 pages per month																											
Copies	6-part forms																											
Throughput	540 pages per hour (ECMA 132/6.91, draft)																											
Graphic Resolution (VxH)	Up to 360 x 360 dpi																											
Character Density	(Emulation dependent) 10,12,15,17.1, 20 cpi																											
Line Density	2, 3, 4, 6, 8, 12 lpi																											
Fonts	Draft, Copy Draft, Courier, Roman, Sans Serif, OCR A, OCR B, 15 Bar Codes & scaleable LCP fonts																											
Emulations	GENICOM ANSI, Epson® LQ-2550, Epson® LQ-2170 (ESC P/2), MTPL																											
Paper Handling	Standard: Front insertion, Push tractor with paper parking and AGA. Options: Additional front push tractor																											
Consumables	20 M Character Ribbon																											
Noise Level	53 dB(A) (ISO 7779)																											
MTBF	10,000 hours @ 25% duty cycle																											
Environmental	+10°C to +35°C (temperature); 16% to 73% (relative humidity)																											
Power Requirements	AC 230V, 50/60Hz and 120V, 60Hz (selectable)																											
Power Consumption	60 Watts																											
Physical (WxDxH)	24.5" x 16.9" x 10.9"; 42 lbs.																											
Interfaces	Standard: Bi-directional Centronics Parallel and RS-232 Serial (auto-switching); 128K buffer Optional: 10/100 Ethernet																											
Warranty	90 days on-site; One year parts																											



BSEN ISO 9001: 1994
Certificate No. FM
28149

 **TallyGenicom®**
4500 Daly Drive, Suite 100
Chantilly, VA 20151

T 800.436.4266
www.tallygenicom.com